

SAFETY DATA SHEET

Unleaded 91



Section 1. Identification

GHS product identifier Unleaded 91
Other means of identification regular unleaded petrol
Product code 0000002733
SDS no. 0000002733
Historic SDS no. 875; 0000002889

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture Use only as a motor fuel for spark ignition engines. NOT for aviation use. Should NOT be used as a solvent nor cleaning agent.
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Manufacturer
Supplier BP Australia Pty Ltd
Level 17, 717 Bourke Street
Docklands, Victoria 3008
ABN 53 004 085 616

www.bp.com.au

EMERGENCY TELEPHONE NUMBER Technical Helpline Number: 1300 139 700
1800 638 556

Section 2. Hazard(s) identification

Classification of the substance or mixture FLAMMABLE LIQUIDS - Category 1
SKIN CORROSION/IRRITATION - Category 2
GERM CELL MUTAGENICITY - Category 1B
CARCINOGENICITY - Category 1B
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3
ASPIRATION HAZARD - Category 1

GHS label elements

Hazard pictograms



Signal word

Hazard statements

DANGER

H224 - Extremely flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H340 - May cause genetic defects.
H350 - May cause cancer.

Precautionary statements

General

P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

Product name Unleaded 91

Product code 0000002733

Page: 1/17

Version 4.01 **Date of issue** 5/26/2021

Format Australia

(Australia)

Language ENGLISH

(ENGLISH)

Section 2. Hazard(s) identification

Prevention	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P281 - Use personal protective equipment as required. P280 - Wear protective gloves, protective clothing and eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241 - Use explosion-proof electrical, ventilating or lighting equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P271 - Use only outdoors or in a well-ventilated area. P261 - Avoid breathing vapour. P264 - Wash hands thoroughly after handling.
Response	P308 + P313 - IF exposed or concerned: Get medical attention. P304 + P340, P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P362 - Take off contaminated clothing and wash before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of soap and water. P332 + P313 - If skin irritation occurs: Get medical attention.
Storage	P405 - Store locked up. P403 + P233 - Store in a well-ventilated place. Keep container tightly closed. P403 + P235 - Keep cool.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	Not applicable.
Other hazards which do not result in classification	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapour may cause flash fire or explosion.

Section 3. Composition and ingredient information

Substance/mixture	Mixture	% (w/w)	CAS number
Gasoline		≥90	86290-81-5
Contains:			
Benzene		<1	71-43-2
Polycyclic aromatic hydrocarbons (PAHs)		<1	mixture
diisopropyl ether		<1	108-20-3
2-methylpropan-2-ol		<1	75-65-0
tert-butyl methyl ether		<1	1634-04-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Inhalation	If inhaled, remove to fresh air. Get medical attention. If exposure to vapour, mists or fumes causes drowsiness, headache, blurred vision or irritation of the eyes, nose or throat, remove immediately to fresh air. Keep patient warm and at rest. If any symptoms persist obtain medical advice.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Drench contaminated clothing with water before removing. This is necessary to avoid the risk of sparks from static electricity that could ignite contaminated clothing. Contaminated clothing is a fire hazard. Contaminated leather, particularly footwear, must be discarded. Clean shoes thoroughly before reuse. Get medical attention.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Aspiration hazard if swallowed. Can enter lungs and cause damage. Get medical attention immediately.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. Product can be aspirated on swallowing or following regurgitation of stomach contents, and can cause severe and potentially fatal chemical pneumonitis, which will require urgent treatment. Because of the risk of aspiration, induction of vomiting and gastric lavage should be avoided. Gastric lavage should be undertaken only after endotracheal intubation. Monitor for cardiac dysrhythmias.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media	In case of fire, use water fog, foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	Extremely flammable liquid and vapour. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Vapours can form explosive mixtures with air. Vapours are heavier than air and can spread along the ground or float on water surfaces to remote ignition sources. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly-grounded containers. Static accumulation may be significantly increased by the presence of small

Section 5. Firefighting measures

Hazardous thermal decomposition products	quantities of water or other contaminants. Liquid will float and may reignite on surface of water. Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide)
Special protective actions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.
Hazchem code	3YE

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Immediately contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. Eliminate all ignition sources.
For emergency responders	Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities. Collect recovered product and other contaminated materials in suitable tanks or containers for recycle, recovery or safe disposal.

Methods and material for containment and cleaning up

Small spill	Eliminate all ignition sources. Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres.
Large spill	Eliminate all ignition sources. Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Dike spill area and do not allow product to reach sewage system and surface or ground water. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilt product. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres. Dispose of via a licensed waste disposal contractor.

Section 6. Accidental release measures

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Do not fill container while it is in or on a vehicle. Static electricity may ignite vapour and cause fire. Place container on ground when filling and keep nozzle in contact with container.

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not swallow. Aspiration hazard if swallowed. Can enter lungs and cause damage. Never siphon by mouth. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Restrict flow velocity according to API 2003 (2008), NFPA 77 (2007), and Laurence Britton, "Avoiding Static Ignition Hazards in Chemical Operations". To reduce potential for static discharge, ensure that all equipment is properly grounded and bonded and meets appropriate electrical classification requirements.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Light hydrocarbon vapours can build up in the headspace of tanks. These can cause flammability/explosion hazards even at temperatures below the normal flash point (note: flash point must not be regarded as a reliable indicator of the potential flammability of vapour in tank headspaces). Tank headspaces should always be regarded as potentially flammable and care should be taken to avoid static electrical discharge and all ignition sources during filling, ullaging and sampling from storage tanks. Do not enter storage tanks. If entry to vessels is necessary, follow permit to work procedures. Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. When the product is pumped (e.g. during filling, discharge or ullaging) and when sampling, there is a risk of static discharge. Ensure equipment used is properly earthed or bonded to the tank structure. Electrical equipment should not be used unless it is intrinsically safe (i.e. will not produce sparks). Explosive air/vapour mixtures may form at ambient temperature. If product comes into contact with hot surfaces, or leaks occur from pressurised fuel pipes, the vapour or mists generated will create a flammability or

Section 7. Handling and storage

explosion hazard. Product contaminated rags, paper or material used to absorb spillages, represent a fire hazard, and should not be allowed to accumulate. Dispose of safely immediately after use.

Section 8. Exposure controls and personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Gasoline	ACGIH TLV (United States). TWA: 300 ppm 8 hours. Issued/Revised: 5/1996 TWA: 890 mg/m ³ 8 hours. Issued/Revised: 5/1996 STEL: 500 ppm 15 minutes. Issued/Revised: 5/1996 STEL: 1480 mg/m ³ 15 minutes. Issued/Revised: 5/1996
Benzene	Safe Work Australia (Australia). TWA: 3.2 mg/m ³ 8 hours. Issued/Revised: 4/2003 TWA: 1 ppm 8 hours. Issued/Revised: 4/2003
Polycyclic aromatic hydrocarbons (PAHs)	Safe Work Australia (Australia). TWA: 0.2 mg/m ³ 8 hours.
diisopropyl ether	Safe Work Australia (Australia). STEL: 1300 mg/m ³ 15 minutes. Issued/Revised: 5/1995 STEL: 310 ppm 15 minutes. Issued/Revised: 5/1995 TWA: 1040 mg/m ³ 8 hours. Issued/Revised: 5/1995 TWA: 250 ppm 8 hours. Issued/Revised: 5/1995
2-methylpropan-2-ol	Safe Work Australia (Australia). STEL: 455 mg/m ³ 15 minutes. Issued/Revised: 5/1995 STEL: 150 ppm 15 minutes. Issued/Revised: 5/1995 TWA: 303 mg/m ³ 8 hours. Issued/Revised: 5/1995 TWA: 100 ppm 8 hours. Issued/Revised: 5/1995
tert-butyl methyl ether	Safe Work Australia (Australia). STEL: 275 mg/m ³ 15 minutes. Issued/Revised: 4/2002 STEL: 75 ppm 15 minutes. Issued/Revised: 4/2002 TWA: 92 mg/m ³ 8 hours. Issued/Revised: 4/2002 TWA: 25 ppm 8 hours. Issued/Revised: 4/2002

Section 8. Exposure controls and personal protection

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Chemical splash goggles.

Skin protection

Hand protection

Wear chemical resistant gloves.

Do not re-use gloves. Protective gloves must give suitable protection against mechanical risks (i.e. abrasion, blade cut and puncture). Protective gloves will deteriorate over time due to physical and chemical damage. Inspect and replace gloves on a regular basis. The frequency of replacement will depend upon the circumstances of use.

Recommended: Gloves made from fluoroelastomer resistant to hydrocarbons and a wide range of chemicals.

Wear a chemically resistant multi-layer laminate inner glove inside an outer nitrile glove. The purpose of the outer glove is to protect the inner glove from cuts and mechanical damage. The presence of aromatic hydrocarbons in the product will significantly shorten the length of time that nitrile gloves will provide protection. Do not re-use nitrile gloves if exposed to aromatic hydrocarbons.

Skin protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Wear suitable protective clothing.

Footwear highly resistant to chemicals.

When there is a risk of ignition wear inherently fire resistant protective clothes and gloves.

When there is a risk of ignition from static electricity, wear anti-static protective clothing. For greatest effectiveness against static electricity, overalls, boots and gloves should all be anti-static.

When the risk of skin exposure is high (from experience this could apply to the following tasks: cleaning work, maintenance and service, filling and transfer, taking samples and cleaning up spillages) then a chemical protective suit and boots will be

Section 8. Exposure controls and personal protection

	required. Work clothing / overalls should be laundered on a regular basis. Laundering of contaminated work clothing should only be done by professional cleaners who have been told about the hazards of the contamination. Always keep contaminated work clothing away from uncontaminated work clothing and uncontaminated personal clothes.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Use with adequate ventilation. If there is a requirement for the use of a respiratory protective device, but the use of breathing apparatus (independent of ambient atmosphere) is not required, then a suitable filtering device must be worn. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.
	Recommended: Avoid breathing of vapours, mists or spray. Select and use respirators in accordance with AS/NZS 1715/1716. When mists or vapours exceed the exposure standards then the use of the following is recommended: Approved respirator with organic vapour and dust/mist (Type P1) filters. Filter capacity and respirator type depends on exposure level.
Refer to standards:	Respiratory protection:AS/NZS 1715 and AS/NZS 1716 Gloves:AS/NZS 2161.1 Eye protection:AS/NZS 1336 and AS/NZS 1337

Section 9. Physical and chemical properties

Appearance

Physical state	Liquid. Clear and Bright
Colour	Pale colour. Yellow. to Red.
Odour	Hydrocarbon.
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Boiling point	30 to 210°C (86 to 410°F)
Flash point	Closed cup: <-40°C (<-40°F)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Lower: 1.4% Upper: 7.6%
Vapour pressure	30.1 to 100.3 kPa (225.6 to 752 mm Hg)
Vapour density	>1 [Air = 1]
Relative density	Not available.
Density	710 to 750 kg/m ³ (0.71 to 0.75 g/cm ³)
Solubility	insoluble in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	>350°C (>662°F)
Decomposition temperature	Not available.
Viscosity	Kinematic: 0.4 to 0.55 mm ² /s (0.4 to 0.55 cSt) at 40°C
Remarks	Reid vapor pressure (RVP): 55 to 100 kPa (40 °C)

Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Avoid excessive heat.
Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Gasoline	LC50 Inhalation Vapour	Rat	>7630 mg/m ³	4 hours
	LC50 Inhalation Vapour	Rat	Nominal >5610 mg/m ³	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapour	Rat	40.5 mg/m ³	1 hours
	LD50 Dermal	Rabbit	2000 mg/kg	-
2-methylpropan-2-ol	LD50 Oral	Rat	8470 mg/kg	-
	LC50 Inhalation Vapour	Rat	>10000 ppm	4 hours
	LD50 Oral	Rabbit	3559 mg/kg	-
tert-butyl methyl ether	LD50 Oral	Rat	2743 mg/kg	-
	LC50 Inhalation Vapour	Rat	85 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Gasoline	Skin - Irritant	Rabbit	-	-	-
	Eyes - Non-irritating to the eyes.	Rabbit	-	-	-
tert-butyl methyl ether	Skin - Irritation	Rabbit	-	-	-
	Eyes - Non-irritating to the eyes.	Rabbit	-	-	-

Skin

Causes skin irritation.

Skin

Not classified. Based on available data, the classification criteria are not met.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Gasoline	Equivalent to OECD 476	Experiment: In vitro Subject: Mammal - species unspecified	Negative
	Equivalent to OECD 471	Experiment: In vitro	Negative
	EPA OPPTS 870.5395	Subject: Non-mammalian species Experiment: In vivo Subject: Unspecified Cell: Germ	Negative
	Equivalent to OECD 475	Experiment: In vivo	Negative

Section 11. Toxicological information

tert-butyl methyl ether	EU B 13/14	Subject: Unspecified Cell: Germ Experiment: In vitro	Negative
	OECD 471	Subject: Non-mammalian species Experiment: In vitro	Negative
	OECD 476	Subject: Non-mammalian species Experiment: In vitro	Negative
	Equivalent to OECD 473	Subject: Non-mammalian species Experiment: In vitro	Negative
	Equivalent to OECD 486	Subject: Non-mammalian species Experiment: In vivo	Negative
	Equivalent to EPA OPPTS 870.5385	Subject: Unspecified Cell: Somatic Experiment: In vivo	Negative
	Equivalent to EPA OPPTS 798.5385	Subject: Unspecified Cell: Somatic Experiment: In vivo	Negative
		Subject: Unspecified Cell: Somatic	

Conclusion/Summary May cause genetic defects.

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Gasoline	Negative - Inhalation - Unspecified	Rat	-	113 weeks
	Negative - Dermal - Unspecified	Mouse	-	102 weeks
tert-butyl methyl ether	Positive - Inhalation - Unspecified	Rat	-	2 years

Conclusion/Summary May cause cancer

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
Gasoline	-	Negative	-	Rat	Inhalation	2 generation
tert-butyl methyl ether	-	-	Negative	Rat	Inhalation	14 days
	-	Negative	-	Rat	Inhalation	2 generation
	-	-	Negative	Rat	Inhalation	9 days

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Gasoline	Category 3	-	Narcotic effects
Benzene	Category 3	-	Respiratory tract irritation
diisopropyl ether	Category 3	-	Narcotic effects
	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Benzene	Category 1	-	blood system

Section 11. Toxicological information

Aspiration hazard

Name	Result
Gasoline	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact	No known significant effects or critical hazards.
Inhalation	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	Causes skin irritation.
Ingestion	Irritating to mouth, throat and stomach. Aspiration hazard if swallowed -- harmful or fatal if liquid is aspirated into lungs.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	Adverse symptoms may include the following: irritation redness
Ingestion	Adverse symptoms may include the following: nausea or vomiting

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact	Vapour, mist or fume may cause eye irritation. Exposure to vapour, mist or fume may cause stinging, redness and watering of the eyes.
Inhalation	Vapour, mist or fume may irritate the nose, mouth and respiratory tract.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Ingestion	If swallowed, may irritate the mouth, throat and digestive system. If swallowed, may cause abdominal pain, stomach cramps, nausea, vomiting, diarrhoea, dizziness and drowsiness.
General	Solvent "sniffing" (abuse) or intentional overexposure to vapours can produce serious central nervous system effects, including unconsciousness, and possibly death.
Carcinogenicity	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	May cause genetic defects.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value						
Product name	Unleaded 91						
Version	4.01	Date of issue	5/26/2021	Product code	0000002733	Page:	11/17
Format	Australia	Language	ENGLISH				
	(Australia)		(ENGLISH)				

Section 11. Toxicological information

Inhalation (vapours)

1156.79 mg/l

Other information

Gasoline - Excess exposure to vapors may produce headaches, dizziness, nausea, drowsiness, irritation of eyes, nose and throat and central nervous system depression. Aspiration of this material into the lungs can cause chemical pneumonia and can be fatal. Aspiration into the lungs can occur while vomiting after ingestion of this product. Inhalation of unleaded gasoline vapors did not produce birth defects in laboratory animals. Ingestion of this material can cause gastrointestinal irritation and diarrhea.

In a long-term inhalation study of whole unleaded gasoline vapors, exposure-related kidney damage and kidney tumors were observed in male rats. Similar kidney effects were not seen in female rats or in mice. At the highest exposure level (2056 ppm), female mice had an increased incidence of liver tumors. Results from subsequent scientific studies have shown that a broad variety of chemicals cause these kidney effects only in the male rat. Further studies have discovered the means by which the physiology of the male rat uniquely predispose it to these effects. Consequently, the Risk Assessment Forum of the Environmental Protection Agency has recognized that these responses are not predictive of a human health hazard. The liver tumors that were increased in the high-dose female mice are likewise of questionable significance because of their high spontaneous occurrence even without chemical exposure and because the rate of their occurrence is accelerated by a broad spectrum of chemicals not commonly considered to be carcinogens (e.g., phenobarbital). Thus, the significance of the mouse liver tumor response in terms of human health is questionable.

Gasoline is a complex mixture of hydrocarbons and contains benzene (typically no more than 2 volume%), toluene, and xylene. Chronic exposure to high levels of benzene has been shown to cause cancer (leukemia) in humans and other adverse blood effects (anemia). Benzene is considered a human carcinogen by IARC, NTP and OSHA. Over exposure to xylene and toluene can cause irritation to the upper respiratory tract, headache and narcosis. Some liver damage and lung inflammation were seen in chronic studies on xylene in guinea pigs but not in rats.

Solvent "sniffing" (abuse) or intentional overexposure to vapors can produce serious central nervous system effects, including unconsciousness, and possibly death.

Gasoline: Additional toxicity information on components.

Overexposure to n-hexane may cause progressive and potentially irreversible damage to the peripheral nervous system, particularly in the arms and legs. Studies in occupationally exposed individuals indicate that toluene exposure has been associated with impaired color vision and decreased performance in some neurobehavioral tests.

Prolonged high level exposure to toluene or xylene has caused some degree of hearing loss in experimental animals.

Inhalation of very high concentrations of gasoline vapors and some of its components can result in cardiac sensitization and irregular heartbeats, leading to potentially fatal changes in heart rhythms. Injection of adrenaline-like agents may enhance this effect.

Benzene: Acute toxicity of benzene results primarily from depression of the central nervous system (CNS). Inhalation of concentrations over 50 ppm can produce headache, lassitude, weariness, dizziness, drowsiness, or excitation. Exposure to very high levels can result in unconsciousness and death.

Section 11. Toxicological information

Benzene: Long-term overexposure to benzene has been associated with certain types of leukemia in humans. In addition, the International Agency for Research on Cancer (IARC), the National Toxicology Program, and OSHA consider benzene to be a human carcinogen. Chronic exposures to high levels of benzene have been reported to cause adverse blood effects including anemia. Benzene exposure can occur by inhalation and absorption through the skin.

Inhalation and forced feeding studies of benzene in laboratory animals have produced a carcinogenic response in a variety of organs, including possibly leukemia, other adverse effects on the blood, chromosomal changes and some effects on the immune system. Exposure to benzene at levels up to 300 ppm did not produce birth defects in animal studies; however, exposure to higher dosage levels resulted in a reduction of body weight of the rat pups (fetotoxicity). Changes in the testes have been observed in mice exposed to benzene at 300 ppm, but reproductive performance was not altered in rats exposed to benzene at the same level. Aspiration of this material into the lungs can cause chemical pneumonia and can be fatal. Aspiration into the lungs can occur while vomiting after ingestion of this material.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Gasoline	Acute EC50 15.41 mg/l Nominal Fresh water	Micro-organism	40 hours
	Acute EL50 3.1 mg/l Nominal Fresh water	Algae	72 hours
	Acute EL50 3.7 mg/l Nominal Fresh water	Algae	96 hours
	Acute EL50 4.5 mg/l Nominal Fresh water	Daphnia	48 hours
	Acute LL50 10 mg/l Nominal Fresh water	Fish	96 hours
	Acute LL50 8.2 mg/l Nominal Fresh water	Fish	96 hours
	Acute NOELR 0.5 mg/l Nominal Fresh water	Algae	72 hours
	Acute NOELR 0.5 mg/l Nominal Fresh water	Daphnia	48 hours
	Chronic EL50 10 mg/l Nominal Fresh water	Daphnia	21 days
	Chronic EL50 >40 mg/l Nominal Fresh water	Daphnia	21 days
	Chronic EL50 10 mg/l Nominal Fresh water	Fish	21 days
	Chronic LL50 5.2 mg/l Nominal Fresh water	Fish	14 days
	Chronic NOELR 2.6 mg/l Nominal Fresh water	Daphnia	21 days
	Chronic NOELR 16 mg/l Nominal Fresh water	Daphnia	21 days
	Chronic NOELR 2.6 mg/l Nominal Fresh water	Fish	14 days
	Chronic NOELR 2.6 mg/l Nominal Fresh water	Fish	21 days
	Chronic PNEC >0.4 mg/kg	soil, plants	-
tert-butyl methyl ether	Acute EC50 472 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 200 mg/l Marine water	Crustaceans	96 hours
	Acute LC50 672 mg/l Fresh water	Fish	96 hours
	Acute LC50 574 mg/l Marine water	Fish	96 hours
	Chronic NOEC 26 mg/l Marine water	Crustaceans	28 days
	Chronic NOEC 51 mg/l Fresh water	Daphnia	21 days

Section 12. Ecological information

Conclusion/Summary

Toxic to aquatic life with long lasting effects.

Persistence and degradability

Expected to be biodegradable. Non-persistent per IMO criteria

Product/ingredient name	Test	Result	Dose	Inoculum
tert-butyl methyl ether	not guideline	100 % - 1.25 days	-	-
	Modelled data	61 to 69 % - 151 days	-	-
	OECD 301 D	9.24 % - Not readily - 28 days	-	-
	OECD 301 D	1.8 % - Not readily - 28 days	-	-
	OECD 301 D	0 % - Not readily - 28 days	-	-
	Modelled data	0 % - 250 days	-	-
Product/ingredient name	Aquatic half-life		Photolysis	Biodegradability
Gasoline	-		-	Inherent

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP _{ow}	BCF	Potential
Gasoline	2 to 7	-	high
Benzene	2.13	11	low
diisopropyl ether	2.4	-	low
2-methylpropan-2-ol	0.317	-	low
tert-butyl methyl ether	1.04	1.5	low

Mobility in soil

Soil/water partition coefficient (K_{oc})

Not available.

Mobility

Spillages may penetrate the soil causing ground water contamination.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Special Precautions for Landfill or Incineration

No additional special precautions identified.

Section 14. Transport information

	ADG	IMDG	IATA
UN number	UN1203	UN1203	UN1203
UN proper shipping name	MOTOR SPIRIT or GASOLINE or PETROL	MOTOR SPIRIT or GASOLINE or PETROL. Marine pollutant	MOTOR SPIRIT or GASOLINE or PETROL
Transport hazard class(es)	3 	3  	3 
Packing group	II	II	II
Environmental hazards	No.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Additional information	<u>Hazchem code</u> 3YE <u>Initial emergency response guide</u> 14	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Emergency schedules</u> F-E, S-E	The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user Not available.

Transport in bulk according to IMO instruments Proper shipping name MARPOL Annex 1 rules apply for bulk shipments by sea.

Category: gasoline and spirits

Section 15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons

Not scheduled. When packed in containers having capacity of greater than 20 litres.

S5. When packed in containers having capacity of less than 20 litres.

Model Work Health and Safety Regulations - Scheduled Substances

Ingredient name	Schedule
Benzene	Restricted carcinogen [All uses involving benzene as a feedstock containing more than 50% of benzene by volume; Restricted use - Genuine research or analysis; For spray painting if the substance contains more than 1% by volume]

Montreal Protocol

Ingredient name	List name	Status
Not listed.		

Stockholm Convention on Persistent Organic Pollutants

Ingredient name	List name	Status
Not listed.		

Rotterdam Convention on Prior Informed Consent (PIC)

Product name	Unleaded 91	Product code	0000002733	Page: 15/17
Version	4.01	Date of issue	5/26/2021	Format Australia (Australia)

Language ENGLISH
(ENGLISH)

Section 15. Regulatory information

Ingredient name	List name	Status
Not listed.		

International lists

National inventory

REACH Status	For the REACH status of this product please consult your company contact, as identified in Section 1.
Australia inventory (AICS)	Contact local supplier or distributor.
Canada inventory	Not determined.
China inventory (IECSC)	Not determined.
Japan inventory (ENCS)	Not determined.
Korea inventory (KECI)	At least one component is not listed.
Philippines inventory (PICCS)	Not determined.
Taiwan Chemical Substances Inventory (TCSI)	Not determined.
United States inventory (TSCA 8b)	Not determined.

Section 16. Any other relevant information

History

Date of printing	5/26/2021
Date of issue/Date of revision	5/26/2021
Date of previous issue	5/25/2021
Version	4.01
Prepared by	Product Stewardship
Key to abbreviations	ADG = Australian Dangerous Goods ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) NOHSC = National Occupational Health and Safety Commission REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006] STEL = Short term exposure limit SUSMP = Standard Uniform Schedule of Medicine and Poisons UN = United Nations TWA = Time weighted average VOC = Volatile Organic Compound SADT = Self-Accelerating Decomposition Temperature Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Procedure used to derive the classification

Product name Unleaded 91

Product code 0000002733 **Page:** 16/17

Version 4.01 **Date of issue** 5/26/2021

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)

Section 16. Any other relevant information

Classification	Justification
FLAMMABLE LIQUIDS - Category 1	On basis of test data
SKIN CORROSION/IRRITATION - Category 2	Calculation method
GERM CELL MUTAGENICITY - Category 1B	Expert judgment
CARCINOGENICITY - Category 1B	Expert judgment
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

 Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

COSHH Risk Assessment		Petrol					
Describe the activity or work process.	Petrol may be added for fire effects such as the use of flame ejectors and fuel bangs. Due to the heat from these effects, the smoke almost entirely raises into the air and dissipates rather than lingering at ground level. Quantities can vary						
Location of process being carried out?	External workshop, Back lot, external locations.						
Identify the persons at risk:	Employees (including trainees) <input checked="" type="checkbox"/>	Contractors <input checked="" type="checkbox"/>	Public <input checked="" type="checkbox"/>				
Name the substance involved in the process and its manufacturer.	Petrol Fuel – Various suppliers						
Classification (state the category of danger)							
<input type="checkbox"/> Toxic	<input type="checkbox"/> Oxidising	<input type="checkbox"/> Respiratory sensitisier					
<input checked="" type="checkbox"/> Irritant Eyes	<input checked="" type="checkbox"/> Flammable	<input type="checkbox"/> systemic target organ toxicity,					
<input checked="" type="checkbox"/> Irritant Skin	<input type="checkbox"/> Gas Under Pressure	<input checked="" type="checkbox"/> Aspiration hazard					
<input type="checkbox"/> Corrosive	<input type="checkbox"/> Explosive	<input checked="" type="checkbox"/> Harmful to the environment					
Hazard Type							
<input type="checkbox"/> Gas	<input checked="" type="checkbox"/> Vapour	<input checked="" type="checkbox"/> Mist	<input checked="" type="checkbox"/> Fume	<input type="checkbox"/> Dust	<input checked="" type="checkbox"/> Liquid	<input type="checkbox"/> Solid	<input type="checkbox"/> Other (State)
Route of Exposure							
<input checked="" type="checkbox"/> Inhalation	<input checked="" type="checkbox"/> Skin	<input checked="" type="checkbox"/> Eyes	<input checked="" type="checkbox"/> Ingestion	<input type="checkbox"/> Other (State)			
Workplace Exposure Limits (WELs) please indicate n/a where not applicable							
Long-term exposure level (8hrTWA): Benzene 3 mg/m ³ Ethanol 1920 mg/m ³ Ethylbenzene 441 mg/m ³ Methanol 266 mg/m ³ n-Hexane 72 mg/m ³ Propan-2-ol (Isopropanol) 999 mg/m ³ Toluene (skin) 191 mg/m ³ Trimethylbenzenes, all isomers or mixtures 125 mg/m ³ Xylene, all isomers (skin) 220 mg/m ³		Short-term exposure level (15 mins): Ethylbenzene 552 mg/m ³ Methanol 233 mg/m ³ Propan-2-ol (Isopropanol) 1250 mg/m ³ Toluene (skin) 574 mg/m ³ Xylene, all isomers (skin) 441 mg/m ³					

State the Risks to Health from Identified Hazards

Classification -

H226: Flammable liquid and vapour.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H336: May cause drowsiness or dizziness.
 H411: Toxic to aquatic life with long lasting effects.

Control Measures:

Used for Fire effect

To be used away from persons, flammables, equipment and vegetation.
 To be used only under the supervision of experienced SFX personnel.
 To be burned as an effect in well-ventilated areas only.
 Crew to be positioned away from smoke
 Minimal to be used to achieve effect.
 Extinguishers to be on standby
 See task risk assessment for specifics.

Storage

Store away from sources of ignition and out of direct sunlight.
 Store in designated and marked containers
 Ensure lid is on tight when not in use.
 Do not store with oxidising agents.
 No smoking signs to be added where necessary.
 Spill kits to be available.

Handling

Gloves to be worn when pouring into containers.
 Eye protection to be worn where there is a risk of splashing.

Environmental

Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways

Is health surveillance or monitoring required?

Yes

No

Personal Protective Equipment (state type and standard)

 <input type="checkbox"/>		 <input type="checkbox"/>	
 <input type="checkbox"/>		 <input checked="" type="checkbox"/>	Goggles and or face shield is splashes are anticipated, EN 166
 <input checked="" type="checkbox"/>	Work gloves providing adequate chemical resistance. EN 374 compliant	 <input checked="" type="checkbox"/>	Skin protection may be required based on use.
 <input type="checkbox"/>		 <input type="checkbox"/>	Other

First Aid Measures

Inhalation:

Move the person to fresh air at once. Seek medical attention if irritation continues.

Eye exposure:

Rinse eyes thoroughly – contact physician if irritation persists

Ingestion:

Do not induce vomiting – wash mouth out with water - get medical attention if discomfort continues

Skin contact

Drench skin with plenty of water, remove contaminated clothing and wash before re-use – seek medical attention if irritation persists

Storage

Store away from sources of ignition and out of direct sunlight.

Store in designated and marked containers

Ensure lid is on tight when not in use.

Do not store with oxidising agents.

No smoking signs to be added where necessary.

Spill kits to be available

CO2 extinguisher to be near storage

Disposal of Substances & Contaminated Containers

Hazardous Waste – Spills are to be put in the hazardous waste bin.

(If Other Please State): recycling or incineration at an approved installation.

Is exposure adequately controlled?

These measures rely on other departments being able to follow them.

Yes

No

Risk Rating Following Control Measures

High

Medium

Low

Assessed By: Dan Scott

Date: 19.11.2024